



Technical Data Sheet

Campaign Banner

Product Description

Campaign Banner is a frontlit 440gsm economy matt laminated PVC banner, ideal for banners, billboards and display systems. It incorporates a 300x500 denier, 18 x 12 base cloth construction with a high-quality surface that delivers consistent printing performance enabling this material to outperform all other economy 440gsm laminates currently available. It is suitable for UV, Latex, Solvent and Eco-Solvent printing. Available up to 3.2 metres wide.

Material Details

CHARACTERISTICS	METRIC	TEST METHOD
Weight	440gsm	ISO3801:1977
Polyester Fabric	300X500 denier 18x12 fd per inch	DIN600001/DIN EN ISO2060
Type of Coating	PVC	N/A
Tensile Strength	690N/5cm (L)	ISO527/3:1995
	450N/5cm (W)	
Tear Strength	65N (L)	ISO4674/1:2003
	55N (W)	
Temperature	-30°C - 70°C	ISO13934-1:1999
RF Weldable (Heat Sealable)	YES	DIN53354

Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Endutex UK Ltd

Unit 15 Eltisley Business Park, Potton Road,
Abbotsley, Cambridgeshire PE19 6TX

Registered in England and Wales number 14772731, V.A.T. number 444315021
Registered office 61A High Street, Rushden NN10 0RA