



Technical Data Sheet

Charisma

Product Description

Charisma is a 195gsm backlit textile with a smooth, non tacky PU (Polyurethane) coating. This material has a bright white point and is highly resistant to bruising. Its lightweight woven construction allows for slight stretch when installing into SEG frame systems. EN13501-1:2010 B-S1, d0 fire rated.

Material Details

CHARACTERISTICS	METRIC	TEST METHOD
Base Fabric	100% DTY Polyester	
Yarn dTex	300	DIN 53830
Width (cm)	320	ISO22198
Total Weight (g/sqm)	195	DIN 2286-2
Thickness (µm)	250	ISO 9073-2
Flame Resistance	EN13501	DIN 4102-1
Stretch	<1%	

Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Endutex UK Ltd

Unit 15 Eltisley Business Park, Potton Road,
Abbotsley, Cambridgeshire PE19 6TX

Registered in England and Wales number 14772731, V.A.T. number 444315021
Registered office 61A High Street, Rushden NN10 0RA