Publishing Date: 29 May 2024



## **Technical Data Sheet**

FT350

## **Product Description**

FT350 is a 350gsm easy apply, removable self-adhesive fabric wall covering that can be fitted to many surfaces and repositioned while retaining its adhesion without leaving a residue. FT350 has a textured surface, with an excellent white point, is quick drying, water resistant and 'Kiss Cuts' cleanly. Its high opacity prevents the translucency problems associated with comparable products. Ideal for temporary wall covering applications for event, retail and exhibition environments. It is suitable for Eco-Solvent, UV and Latex printing. Available in 1.37 and 1.52 metre rolls.

## **Material Details**

CHARACTERISTICS	METRIC	TEST METHOD
Support Cloth	Polyester	DIN 60001
Yarn dTex	166 x 166	DIN EN ISO 2060
Adhesive	White Repositionable Adhesive	
Opacity	99%	ISO 2471
White Point	90 out of 100	ISO 105-J02: 1997
Total Weight (gsm)	350	ISO 534
Release Paper	Paper Liner 100g (Both sides PE)	
Storage Recommendation	<ul> <li>All Endutex materials should be stored in their original packaging.</li> <li>FT350 should be stored in temperatures between 10° and 20°C and a relative humidity of 20% - 60%.</li> </ul>	
Flame Retardant	Non Fire Rated	

## **Disclaimer**

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.