

**Product Description**

Polycril 275 FR from the Terratex range of materials is a 100% PVC free textile canvas material. This 275g woven material has an acrylic coating which gives the material a slight canvas like finish. It is highly dimensionally stable with great lay flat capabilities. Its coating provides a dirt resistant wipe clean surface. Suitable for Solvent, UV and Latex inks it has an EN13501 fire certification for the most demanding of internal applications. Available up to 5m wide.

Material Details

CHARACTERISTICS	METRIC	TEST METHOD
Thickness (mm)	0.30	
Total Mass (g/m ²)	275 ± 25	EN ISO 2286-2
Fabric Mass (g/m ²)	145 ± 10	EN ISO 2286-2
Breaking Load (daN/50mm)	L: 1500 T: 850	EN ISO 1421
Tear Strength (N)	L: 200 T: 100	DIN 53363
Burning Behaviour	B1	DIN 4102
Burning Behaviour	B s2 d0	EN 13501-1

L – Along | T – Across

Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.