Publishing Date: 25 July 2024



## **Technical Data Sheet**

# **Print LM**

### **Product Description**

Print LM is a frontlit 440gsm economy matt laminated PVC banner. It incorporates a 1,000  $\times$  1,000 denier, 12  $\times$  12 base cloth construction ensuring excellent tear and tensile strength. With a high-quality surface that delivers consistent printing performance enabling this material to outperform all other economy 440gsm laminates currently available. It is suitable for Eco-Solvent, UV and Latex printing. Available up to 3.2 metres wide.

#### **Material Details**

CHARACTERISTICS	METRIC	TEST METHOD
Support Cloth (Weave)	Polyester (12 x 12)	DIN 2076
Yarn (Thickness)	1000×1000	DIN EN ISO 2060
Type of Coating	PVC	DIN 53352
Total Weight (gsm)	440gsm	DIN 53352
Tensile Strength (Warp / Weft)	1,850 / Welf N/5cm	DIN 53352
Tear Strength (Warp / Weft)	350 / 300 N	DIN 53356
Flame Retardant	Non Fire Rated	
Low Temperature (No Crack at:)	-20°C	DIN 53357
RF Weldable (Heat Sealable)	V	

#### Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.