

Technical Data Sheet

Print PA FR

Product Description

Print PA is a 450gsm knife coated PVC banner material specially developed for frontlit applications. Its construction and coating are optimised for tension framing systems. It is EN13501 B2 s2 d0 fire rated. Suitable for Solvent UV and Latex inks. Available up to 5m wide.

Material Details

CHARACTERISTICS	METRIC	TEST METHOD
Thickness (mm)	0.40	
Total Mass (g/m ²)	450 ± 40	EN ISO 2286-2
Fabric Mass (g/m ²)	130 ± 10	EN ISO 2286-2
Breaking Load (daN/50mm)	L: 240 T: 140	EN ISO 1421
Tear Strength (daN)	L: 25 T: 20	DIN 53363
Coating Adhesion (daN/50mm)	Min. 5	EN ISO 2411
Colour Fastness to Light	Min. 6	EN ISO 105-B02
Burning Behaviour	B1	DIN 4102
Burning Behaviour	B s1 d0	EN 13501-1

L – Along | T – Across

Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Endutex UK Ltd

Unit 15 Eltisley Business Park, Potton Road,
Abbotsley, Cambridgeshire PE19 6TX

Registered in England and Wales number 14772731, V.A.T. number 444315021
Registered office 61A High Street, Rushden NN10 0RA