Publishing Date: 29 May 2024



Technical Data Sheet

Pro Blockout 610

Product Description

Pro Blockout 610 is a double-sided banner incorporating 500×500 denier, 28×28 woven base cloth construction. Having a high-quality hybrid / semi-coated smooth and even surface on both sides combined with a woven base cloth means excellent print and lay flat consistency unlike other lighter weight products. It is ideal for indoor and outdoor applications under moderate weather conditions. It is suitable for Eco-Solvent, UV and Latex printing and is B1 fire rated. Available up to 5 metres.

Material Details

CHARACTERISTICS	METRIC	TEST METHOD
Support Cloth (Weave)	Polyester (28 x 28)	DIN 60001
Yarn (Thickness)	500 x 500	DIN EN ISO 2060
Type of Coating	PVC	N/A
Total Weight (gsm)	610	DIN 53352
Tensile Strength (Warp / Weft)	1,850 / 1,350 N/5cm	DIN 53352
Tear Strength (Warp / Weft)	235 / 220 N	DIN 53356
Flame Resistance	EN13501	DIN 75200
Low Temperature (No Crack at:)	-20°C	DIN 53357
RF Weldable (Heat Sealable)	V	

Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.