



### Product Description

Strip Mesh is a 270gsm (with 1,000 x 1,000 denier, 12 x 12 knitted base cloth) PVC Mesh that allows 25% air flow through the material and comes with a protective backing liner. It has excellent product consistency unlike many of its rivals and is reliable when used with Latex inks. The material is ideally suited for fence dressing or other short-term applications. It is recommended for use with Latex, Eco-Solvent and UV inks, B1 fire rated. Available up to 3.2 metres wide.

### Material Details

CHARACTERISTICS	METRIC	TEST METHOD
<b>Support Cloth</b> (Weave)	Polyester (12 x 12)	DIN 60001
<b>Yarn</b> (Thickness)	1000 x 1000	DIN 53352
<b>Type of Coating</b>	PVC	N/A
<b>Weight of PVC Liner</b>	100gsm	DIN 53352
<b>Total Weight</b> (Mesh) (gsm)	270	DIN 53352
<b>Tensile Strength</b> (Warp / Weft)	1,250 / 1,100	DIN 53352
<b>Tear Strength</b> (Warp / Weft)	235 / 225	DIN 53352
<b>RF Weldable</b> (Heat Sealable)	✓	DIN 53354
<b>Flame Retardant</b>	B1	DIN 4102
<b>Air Permeability</b> (mm/s)	2649	GB/T 2410-2008
<b>Light Transmission</b>	37%	GB/T 5453-1997
<b>Low Temperature</b> (No Crack at:)	-20°C	DIN 53357

### Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.