



# Technical Data Sheet

## Soft Floor

### Product Description

Soft Floor is an 850g PVC-coated polyester woven fabric designed for high-impact retail and event environments. Ideal for in-store advertising, pop-up retail installations, exhibition flooring, and window displays, it offers excellent dimensional stability and slip resistance.

Compatible with Solvent, UV, and Latex inks, Soft Floor also meets EN13501 B fl-S1 fire safety standards and is available in widths up to 3.2 metres.

CHARACTERISTICS	METRIC	TEST METHOD
Thickness (mm)	1.80 ± 0.20	
Composition	83% PVC 17% Polyester	
Total Mass (g/m <sup>2</sup> )	850 ± 60	EN ISO 2286-2
Fabric Mass (g/m <sup>2</sup> )	145 ± 10	EN ISO 2286-2
Breaking Load (daN/50mm)	L : 1400 T : 800	EN ISO 1421
Breaking Extension (%)	L : 20 T : 20	EN ISO 1421
Tear Strength (daN)	L : 25 T : 25	EN ISO 4674-1B
Slip Resistance	Class DS	EN 13893
Slip Resistance	R9	DIN 51130
Burning Behaviour	B fl-S1	EN 13501-1

L - Along T - Across

### Disclaimer

This technical data sheet is not legally binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. The purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

#### Endutex UK Ltd

Unit 15 Eltisley Business Park, Potton Road,  
Abbotsley, Cambridgeshire PE19 6TX

Registered in England and Wales number 14772731, V.A.T. number 444315021  
Registered office 61A High Street, Rushden NN10 0RA